

Platinum320 Series


OUTDOOR SOLUTIONS

Key Features:

- Die-casting aluminum module for fast heat dissipation.
- IP68 waterproof and 5VB fireproof.
- CCES energy-saving technology.
- High brightness option for 10,000nits.
- Totally front and rear service.
- Stable and reliable performance.




Standard Dimension: 1,280x960x90mm
Optional Dimensions: 1,280x960mm/1,280x1,280mm/960x960mm/960x1,280mm
Pixel Pitch: 4.4mm, 5.7mm, 6.67mm, 8mm, 10mm
Applications: Digital signage, billboard, road sign, stadium scoreboards, building facade,etc.



Die-casting aluminum module for fast heat dissipation



Hidden cable cover, protect the power cable and signal cable from damages.



Perfect seamless corner cabinet for naked-eye 3D solution.



Die-casting connecting plate, for wall-mount installation directly.

Item Number	FAB-PT320 4.4	FAB-PT320 5.7	FAB-PT320 6.67	FAB-PT320 8	FAB-PT320 10
Pixel Pitch(mm)	4.44	5.71	6.67	8	10
Pixel Density(dots/SQM)	50,625	30,625	22,500	15,625	10,000
LED Type	SMD1935	SMD2727	SMD2727	SMD3535	SMD3535
Module Resolution(pixels)	72*72	56*56	48*48	40*40	32*32
Module Size(mm)	320*320	320*320	320*320	320*320	320*320
Cabinet Size(mm)	1280*960	1,280*960	1,280*960	1,280*960	1,280*960
Cabinet Weight(KG/m²)	28	30	30	30	30
Brightness(Nits)	6,000–8,000	6,000–10,000	6,000–10,000	6,000–10,000	6,000–10,000
Refreshment(Hz)	7,680	7,680	7,680	7,680	7,680
Grey Scale(Bit)	14–16	14–16	14–16	14–16	14–16
Max Power Consumption(W/SQM)	650±5%	600±5%	600±5%	600±5%	600±5%
Ave Power Consumption(W/SQM)	195	180	180	180	180
Maintenance Type	Front/Rear	Front/Rear	Front/Rear	Front/Rear	Front/Rear
Ingress Protection	IP68/IP66	IP68/IP66	IP68/IP66	IP68/IP66	IP68/IP66