

Platinum Mesh Series

OUTDOOR SOLUTIONS

Key Features:

- IP68 waterproof and 5VB fireproof.
- CCES technology, 30% energy saving.
- High brightness option for 10,000nits.
- Lightweight, effortless installation.
- Totally front and rear service.
- The masks feature a screw-lock and latch design to prevent lifting or detachment.



Standard Dimension: 1,000x1,000x86.7mm
Pixel Pitch: 15.6mm, 20.8mm, 31.2mm
Applications: Building facades, retail showcases, outdoor advertising, exhibitions, etc.




Seamless light bar modules, triple waterproof protection.



Power box dual-layer protection



71 % ultra-high transparency, unobstructed views.



Diamond-textured mask for enhanced contrast.

Item Number	FAB-P15.6	FAB-P20.8	FAB-P31.2
Pixel Pitch(mm)	15.625*15.625	20.8333*20.8333	31.25*15.625
Pixel Density(dots/SQM)	4,096	2,304	2,048
LED Type	LIP3747/SMD3535	LIP3747/SMD3535	LIP3747/SMD3535
Module Resolution(pixels)	8*64	4*64	6*48
Module Size(mm)	125*1,000	125*1,000	125*1,000
Cabinet Size(mm)	1,000*1,000/500*1,000	1,000*1,000/500*1,000	1,000*1,000/500*1,000
Cabinet Weight(KG/SQM)	15	13	10
Brightness(Nits)	10,000/8,000	10,000/8,000	10,000/8,000
Refreshment(Hz)	7,680	7,680	7,680
Grey Scale(Bit)	16	16	16
Max Power Consumption(W/SQM)	430±5%/600±5%	430±5%/600±5%	430±5%/600±5%
Ave Power Consumption(W/SQM)	129/180	129/180	129/180
Maintenance Type	Front/Rear		
Ingress Protection	IP68/IP66		
Certificate	CE(LVD, EMC), CB, FCC, ETL		