

Platinum Pro Series

OUTDOOR SOLUTIONS

Key Features:

- 400x300mm aluminum module design for 16:9 golden ratio.
- IP68 waterproof and 5VB fireproof.
- Support power and signal back up.
- CCES energy-saving technology.
- High brightness option to 10,000nits.
- High quality components for 3 years to 5 years warranty.



Dimension: 800x1,200x86mm
Optional Dimensions: 800x600mm/800x900mm/800x1,200mm/1,200x600mm /1,200x900mm/1,200x1,200mm/1,600x900mm
Pixel Pitch: 6.67mm, 8.3mm, 10mm
Applications: Dooh market, billboard advertisement, road sign, stadiums, etc.



400x300mm die-casting aluminum module,for fast heat dissipation



Hard connection design with total front and rear service.



Hidden cable cover, protect the power cable and signal cable from damages.



Die-casting connecting plate, for wall-mount installation directly.

Item Number	FAB-PTP6.67	FAB-PTP8	FAB-PTP10
Pixel Pitch(mm)	6.67	8.3	10
Pixel Density(dots/SQM)	22,500	14,400	10,000
LED Type	SMD2727	SMD2727	SMD3535
Module Resolution(pixels)	60*45	48*36	40*30
Module Size(mm)	400*300	400*300	400*300
Cabinet Size(mm)	800*600/800*900/800*1,200/1,200*600/1,200*900/1,200*1,200/1,600*900		
Cabinet Weight(KG/SQM)	30	30	30
Brightness(Nits)	6,000-10,000	6,000-10,000	6,000-10,000
Refreshment(Hz)	7,680	7,680	7,680
Grey Scale(Bit)	14-16	14-16	14-16
Max Power Consumption(W/SQM)	600±5%	600±5%	600±5%
Ave Power Consumption(W/SQM)	180	180	180
Maintenance Type	Front/Rear	Front/Rear	Front/Rear
Ingress Protection	IP68/IP66	IP68/IP66	IP68/IP66
Certificate	CE(LVD, EMC), ETL, FCC, RoHS		