

Platinum S Series

OUTDOOR SOLUTIONS

Key Features:

- Fine pixel pitch for outdoor fixed installation.
- Die-casting aluminum module for fast heat dissipation.
- IP68 waterproof and 5VB fireproof.
- Easy to service from front and rear side.
- High brightness option to 10,000nits.
- Stable performance for outdoor environment.



Standard Dimension: 500x1,000x81mm
Optional Dimensions: 500x500mm/500x750mm/500x1,000mm
Pixel Pitch Outdoor: 2.9mm, 3.9mm, 4.8mm, 6.25mm
Applications: Window Screen, Digital Signage System, Bus Station, Arena Display, Business Advertising Signs, Airport, etc.



Flexible cabinet size



Cabinet with side cut 45 degree, installed into 90 degree corner.



Cables hidden on top of cabinet, for safety and long lifespan.



Perfect seamless corner cabinet for naked-eye 3D solution.

Item Number	FAB-PTS2.9	FAB-PTS2.9	FAB-PTS3.9	FAB-PTS3.9	FAB-PTS4.8	FAB-PTS6.2
Pixel Pitch(mm)	2.9	2.9	3.9	3.9	4.8	6.2
Pixel Density(dots/SQM)	112,896	112,896	65,536	65,536	43,264	25,600
LED Type	SMD1515 (white led)	SMD1515 (black led)	SMD1935	SMD1921 (white led)	SMD1921 (white led)	SMD2727 (white led)
Module Resolution(pixels)	84*84	84*84	128*64	128*64	104*52	80*40
Module Size(mm)	250*250	250*250	500*250	500*250	500*250	500*250
Cabinet Size(mm)	500*500/500*750/500*1,000					
Cabinet Weight(KG/SQM)	38		36.5			
Brightness(Nits)	4,500-6,000	2,500-3,500	6,000-8,000	5,000-8,000		6,000-10,000
Refreshment(Hz)	7,680					
Grey Scale(Bit)	14-16					
Max Power Consumption(W/SQM)	650±5%	590±5%	650±5%	570±5%	570±5%	600±5%
Ave Power Consumption(W/SQM)	195	177	195	171	171	180
Maintenance Type	Front/Rear					
Ingress Protection	IP68/IP66					
Certificate	CE(LVD、EMC), CB, FCC, ETL, RoHS					